



# Model GB-1575TR

## Available Options

- HP 60, 80, 120, 180
- Cylinder 10" 12"
- Feed Opening (71" x 40") (83" x 56")
- Stamper (not available in combination with sliding lid)
- Sliding Lid
- Fluffer
- Hardox bolt in wear liner package

## GB-1575TR-3018

Model Specifications	180 HP	12" Cylinder	136" Stroke
• Feed opening			71" x 40"
• Bale Chamber			30" x 60" x 136"
• Bale Size expandable			30" x 60" x 43"
• Compressing Cylinder			12" Diameter 136" Stroke
• Push-Out Cylinder			9" Diameter 86" Stroke
• Machine Weight			61,750 lbs.
• Main Baler Body Frame			SS41/HARDOX 400/S50C
• Cutting Knife Replaceable			Tool Steel Scatter Cutter
• Auto Tier			Accent or L&P
• Cycle Time (No Load)			9.4 Sec.
• Cycles Per Minute			6.3
• Production (O.C.C.)			17 - 22 TPH

## Hydraulic System

- Hydraulic System Regenerative
- Oil Reservoir 1,200 Gallons 4600 Liters
- Hydraulic cooling Air Cooling
- Hydraulic filtration Suction Filter
- Hydraulic Pump Brand DENISON
- Valve Brand VICKERS

## Electrical System (UL)

- PLC MITSUBISHI
- Operator Interface Human Machine Interface
- Main Motor Control STAR/DELTA
- Controller Brand Schneider
- UL Standard

## After Service System

- Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

## Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: High tensile galvanized baling wire (3.1 mm DIA), cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.